

BT 700k 700,000BTU/HR



Model Specifications

- Engine:** John Deere 99 HP @ 2,400 RPM
- Hitch Setup:** 2 5/16" Ball Hitch
- Governing:** Electronic - Overspeed Shutdown
- Outlet Duct:** (1) 16" Diameter Outlet W/Four Galvanized Quick Clamps
- Fuel Capacity:** 150 Gallons US
- Heat Transfer Fluid:** ~24 Gallons Synthetic CalFlo or Synthetic ATF
- Run Time:** 26 Hours at 100% Load
- Electric System:** 12 VDC w/100 Amp Alternator
- Air Flow:** 5,000 CFM @ 5.5" H₂O
- Temp Rise:** 140 °F
- Ambient Air Rating:** -40 °F TO + 60 °F
- Air Controller:** Automatic Shutter Controller
- Fuel Efficiency:** 67%+
- Weight:** 5,640 Lbs
- Dms Overall:** 136" L x 68" W x 91" H

Available Options

- Hitch Setup:** Pintle Hitch
- Leveling Jacks:** Rear Corner Mounted Bulldog Jacks
- Dual Axle:** Dual Axle with Steel Fender Extension
- Stainless Hardware:** Stainless Bolt Kit, Exterior Clamps & Bolts
- Electrical System:** 12VDC w/100 Amp Brushless/ Sparkless Alternator
- LED Warning System:** 3 Function Roof Mounted Strobe Lights - On/Off and Low Fuel Indicator
- OPH:** Oil Pan Heater (60 Hz)
- BBH:** Battery Blanket Heater (60 Hz)
- EBH:** Engine Block Heater (60 Hz)
- Stone Guard:** To Roof Line